

6500E Diesel Generator 1 Phase 3600RPM Genset Single **Phase**

Basic Information

. Place of Origin: China . Brand Name: **GET** ISO CE · Certification: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3

6.8

2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 Max Output (kw):

• Rated Voltage (V): 220V Or As Request

7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 • Rated Currency (A):

28.2/28.6 30.9

Rated Rotation Speed

(r/min):

3000 3600 R/min

• Phase No.: Single Phase

Power Factor: 1 Insulation Grade: F Pole Number:

• Excitation Mode: Self-excitation & Constant Voltage (AVR)

· Panel Type: General Panel

Product Description

GET6500E Single Phase Open Type Diesel Generator Open Type Genset

Open type diesel generators have specific features that distinguish them from other types of generators. Here are some detailed features of open type diesel generators:

Cooling System: Open type diesel generators incorporate a cooling system to maintain optimal operating temperature. The cooling system typically includes a radiator, cooling fan, and coolant circulation system. It ensures efficient heat dissipation, preventing the engine from overheating and ensuring reliable performance.

Exhaust System: The generator set includes an exhaust system to safely discharge the combustion gases produced by the diesel engine. The exhaust system typically includes a muffler or silencer to reduce noise levels and may include piping and ventilation components for proper exhaust disposal.

Fuel System: An open type diesel generator incorporates a fuel system for supplying diesel fuel to the engine. It typically includes a fuel tank, fuel filters, fuel lines, and a fuel pump. The fuel system ensures a consistent and reliable fuel supply to the engine for uninterrupted operation.

Safety Features: Open type diesel generators often include safety features to protect the equipment and ensure safe operation. These features may include low oil pressure shutdown, high-temperature shutdown, overcurrent protection, and circuit breakers. They help prevent damage to the generator and ensure the safety of both the generator and connected electrical equipment.

Maintenance and Serviceability: Open type diesel generators are designed for easy maintenance and serviceability. They often feature accessible components, such as removable panels or doors, for convenient inspection, cleaning, and repair. This allows for easier maintenance tasks, reducing downtime and ensuring the generator operates at its optimal performance. Environmental Considerations: It's important to note that open type diesel generators do not have an enclosure, which means they can generate higher noise levels compared to enclosed generators. Additionally, they may be more susceptible to environmental factors such as weather conditions. Additional measures may be required to mitigate noise and protect the generator from adverse weather conditions, depending on the specific application.

Open type diesel generators are commonly used in construction sites, remote locations, agriculture, emergency backup power, and industrial settings where noise levels and environmental factors are less critical. Their compact and portable design, along with their reliable diesel engine power, make them suitable for a wide range of applications.

Patad Output/law):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8				
Rated Output(kw):					
Rated Voltage (V):	220V Or As Request				
Rated Rotation Speed (r/min):	3000 3600				
Power Factor:	1				
	2				
Pole Number:					
Panel Type: Connection Pole:	General Panel				
Connection Pole:	Without				
Overall Dmension(mm):	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ 730x495x630/ 730x495x655				
Working Assorting Weight (kg):	66 83 110 115 120 125				
Structure Type:	Open Type				
Cylinder Nobore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75				
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600				
Lubrication System:	Pressure Splashed				
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40				
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW				
Battery Capacity:	12V 20Ah/ 12V 30Ah				
Fuel Tank Capacity (L):	13.5				
Rated Frequency:	50hz 60hz				
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4				
Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9				
Phase No.:	Single Phase				
Insulation Grade:	F				
Excitation Mode:	Self-excitation & Constant Voltage (AVR)				
Receptacle:	Two Receptacles				
DC 12V Output:	Connection Pole Output				
Dry Weight (kg):	53 70 100 105 110 115				
Noise Level (7m):	77 DB				
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled				
Displacement(ml):	247 296 418 456 498 531				
Compression Ratio:	20:01, 19:01				
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel				
Lube Capacity (L):	0.75 1.1 1.65				
Charging Generator Capacity:	12V 8.3A				
Fuel Consumption (g/kw*h):	≤280				



DE Mass				ORTHUR	DETROOP		
MESSER Rated Requests (1927)	8.8						
MERCH II Rated reday Cit	18.20	23 28	48 50	80 82	63 62	62 68	
BANKS No. motort NO.	23 33	37 38	12 15	88.17	63 63	69.74	
MESS Stated college (V)	SOLVERSE PER SOLVER STORE						
HE B.E Sales narrows A	78.67	113 107	263 257	20.7 23.6	373 363	284 364	
BERNE Rated totalist opposit I close 1	NOT THE						
68 Property.	BIS Targia phone						
MARKET Property areas (Cop. 46)							
MANGE INVESTIGATE							
SR houseby							
BEST Dobero note	BERLS Barry Set workers & contact votage profit						
BERT Poter Type	WARM Sport from						
MICHE RESORDS	BY BERRY BR Too registrate						
MidNett Correctionals	8 RPM						
MISSION TO DOT DY HIGHE	MISSING Connector and Astro						
PRINT Dengl december (Lx Plus 1 1 mm)	exc-serses	8907407360	730'480'030	79014601000	75074807000	797466765	
RED to would that	10	70	100	100	110	778	
MINE PRE Victor marks profit [In]	- 64	80	716	105	100	109	
Mark Strategy State (Sept. 1984)	39	TT	25	TT	77	77	
ATTINE Display has	Service .						
26 State SCHI Conglesia Marini	SETTING	GETCW	SETTIMEN	GETTINE	DET-NOT	GETTHEF	
At Bell Kirk Covins Cove.	Drain cylinder, perhad, buy strate, dred transfers, an scotted						
TARREST BIR Colonia NO. Jones valence mm	1.75%	1.7990	1.8679	1.0075	1.6075	1.6675	
BRE (Nepturament (176.)	20	200	416	150	101	E24	
#ES & Electronic State Longer	25/200 0.8/2000	3.6919000 A-9000	6.1/2000 A-3/2000	5.5/2000 1 (CORDO	T-0-7000 R-2/2000	8.10000 A 7000	
ERR Compression-rate	2004	26.91	100	1991	1994	1001	
MRXX Locutor sitten	Exhibited frames shaped						
BRYS Street area	REST BEST ROOM - DOOR STAT						
BBBS Nation	TF (第3.1-TF (63.1-TF (66.1 (40.1F (aprile) - 67 (airse) - 68 (chines) food						
SHOW THE LAKE OF THE PER	CD 2000 or SAC SIR- SE. 1991-40						
SERVICE Life Intenty (), (0.75		1.80	1.01	130	1.69	
日本日本日本 Dedicated reports (VAN)	129 0.00	TOY DOWN	109 5,966	DV CWW	109 1,009	12V 1,569	
NAZIANES Carps premie specify (Y-1)	UV 63A						
NO. OF STREET, SQUARE, 1 or 50-1	120	Min	101 304		- OT 2000		
MARKET Out organism (short)	- 18						
MARKET Park Set County (). (9.5						
HARD THE CONTRACT SOMETHING IN	- 4	10			7	7	

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506

2415819289@qq.com

e dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA