White 9500T Silent Diesel Generator Electric Start Silent Generator

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time: 15-20 work

China

- Payment Terms:
- GET ISO CE Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



Product Specification

 Rated Frequency: 	50hz 60hz
 Rated Output(kw): 	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
 Max Output (kw): 	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
 Rated Voltage (V): 	220V Or As Request
• Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
 Rated Rotation Speed (r/min): 	3000 3600
Phase No.:	Single Phase
 Power Factor: 	1
 Insulation Grade: 	F
Pole Number:	2
 Excitation Mode: 	Self-excitation & Constant Voltage (AVR)
 Panel Type: 	General Panel
 Receptacle: 	Two Receptacles
Connection Date:	

GET9500T Silent Diesel Generator White Electric Start Silent Generator

Quiet diesel generators come with various features and technologies that contribute to their reduced noise emissions. While the specific features may vary depending on the manufacturer and model, here are some common features found in quiet diesel generators:

Soundproof Enclosure: Quiet diesel generators are typically equipped with a soundproof enclosure or housing made of materials designed to absorb and dampen noise. The enclosure helps to contain the sound and prevent it from escaping, reducing noise levels significantly.

Acoustic Insulation: The soundproof enclosure is lined with acoustic insulation materials, such as foam or specialized noisereducing materials. These materials absorb sound waves, preventing them from bouncing around and reducing the overall noise level.

Smart Load and Speed Control: Some quiet diesel generators come with smart load and speed control features. These systems automatically adjust the engine speed and power output based on the load demand, optimizing fuel consumption and reducing noise levels during low-demand periods.

Noise Level Specifications: Quiet diesel generators are typically rated for noise levels, which are measured in decibels (dB). The noise level specification indicates the sound output at a specific distance from the generator, such as 7 meters (23 feet). Lower dB ratings indicate quieter operation.

Lower ab raings maioate quiete			
Rated Frequency:	50hz 60hz		
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7		
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6		
Phase No.:	Single Phase		
Insulation Grade:	F		
Excitation Mode:	Self-excitation & Constant Voltage (AVR)		
Receptacle:	Two Receptacles		
DC 12V Output:	Connection Pole Output		
Dry Weight (kg):	164 150 150 153 161		
Noise Level (7m):	72 DB		
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled		
Displacement(ml):	296 418 456 498 531		
Compression Ratio:	20:01, 19:01		
Starting System:	Electric Start		
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40		
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW		
Battery Capacity:	12V 30Ah		
Fuel Tank Capacity (L):	15		
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3		
Rated Voltage (V):	220V Or As Request		
Rated Rotation Speed (r/min):	3000 3600		
Power Factor:	1		
Pole Number:	2		
Panel Type:	General Panel		
Connection Pole:	Without		
Overall Dmension(mm):	945*555*700		
Working Assorting Weight (kg):	179 185 186 186 187		
Structure Type:	Silent Type		
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75		
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000- 8.7/3600		
Lubrication System:	Pressure Splashed		
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel		
Lube Capacity (L):	1.1/ 1.65		
Charging Generator Capacity:	12V 8.3A		
Fuel Consumption (g/kw*h):	≤280		



Still Model	OFTIMOT	TIMOT	OFTNEE	BETHNOET	
B283 /Webciteguerry He			52 66		
BEER Paterinsted (10%)	2.8 2.8	4.0 4.8	4.8 8.0	87 60	60.63
BARRIE Man. mapril (1997)	3.7 30	10 13	6.2 6.8	83.62	48.33
BRIGH Plaint-schape (5)	LOV/DRWK PER 200/ or an request				
Bill Bill Photo Survey 14.5	TLS 127	204 218	21.8 22.7	20.8 27.2	373.38.8
EXTRA Partnerships agend Colver 1	2001 2800				
BE Phone MC	WEI DYCH JIGH				
Site 2000 Provent Sector 1 Cost -0 2					
Bill B Di Insulation Erach					
DB Pos number			8		
BREED Excession made	(B.695.3.) (Bank) (Set-auctuation & constant unless and it				
Diskist Panel Type	# 888 General Fand				
et die Prostale		Nº 00000 ES Tax montains			
R & M M & Connection price	8 Autout				
BEDE SIV DESIV odpit		80	RIMA Corrector pole to		
HER-H Granal dimension (LowPublic Creek)	942-902-906	845/555798	941-555700	847/007/108	845-555798
NE Dry anight I to I	*64	-12	+50	123	182
Light States printing analysis (b) 1	178	185	136	484	182
Bill William Management Per	10	72	10	79	72
PORT Tradest light	Hard bare				
DBRBA Dupe Mobil	DETICH	GETINFA	CET HIMP	0071407	GETHEF
Indexed & Drugee Type	Way, X.Y., May, 2016, (Advanted by a particular operation from drawn drawn pression, and pression				
NEE-IEE/WEED/WEED/CONFIGURATION	1-79'80	1-00"72	1-88779	1-8075	1-81'75
IN B Experience I and I	294	4.0	450	498	500
of the second stand proof	3.55/3000 41800	5 20000-0-010000	4-5/9000 P (20000)	1 010000-01210000	81/00014-1008
Citit & Compression ratio	and a second	1001	1991	1004	10111
A R R R Laboration system	En Villehrd Presses schoted				
Grand of chartery system	4 G in Earthe start				
Ball for you	04 (201)-104 (201)-364 (203) 808 dead04 (sense)-364 (sinter)-364 (mines) dead				
internal internal internal	CD mark or SM SIA 31, 1597-80				
Contraction of the second seco	1.1	1.61	1.65	1.65	1.05
101-11 distant when a set of the little	124 8.044	10/ 09/9	101 6.000	124 1.244	107 1,000
I&E B R.R.B. Charging generator stagestic [V-A]	107 8.34	124 8.56	429 4.34	GTV 8.34	124 8.56
DR.R.R.B. Bulley-Learning Cor-Wol		101 3044		UV	MAG
BERRE Functionarytics (gite/%)	+200	< 380	<381	+280	< 380
TRAFFIC Fuelant specty [1.1	10	10	15	11	10
NEEPERM COMMAND AWAY MILETY	11	1			

G ET Wuxi Guangertai Power Machinery Co.,Ltd					
() 1381365	50506 2415819289@qq.com	e dieselenginepumps.com			
NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA					

L