



GET186FA GET192F Diesel Engine Pumps 2.8kw-8.5kw Diesel Water Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

Industrial Diesel Engine Pumps Diesel Water Pump Diesel Fire Pump

A diesel fire pump is a specialized type of pump used specifically for fire protection systems. It is designed to provide a reliable and efficient water supply for firefighting applications in buildings, industrial facilities, and other installations.

A diesel water pump is a type of pump specifically designed for transferring or moving large volumes of water in various applications. These pumps are commonly used in construction sites, agriculture, mining, dewatering, irrigation, and other situations where a reliable and efficient water transfer is required.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	



Model	JBC6/10	JBC6/15	JBC6/15A	JBC6/15B
Model Type	Diesel water pump	Diesel water pump	Diesel water pump	Diesel water pump
Discharge Port Diameter (mm)	50	50	50	50
Max. Flow (T/h)	48	54	54	54
Max. Lift (m)	60	80	80	80
Rated Speed (rpm)	3600	3600	3600	3600
Water Shot Height (m)	35	35	35	35
Engine	190F	192	192	192
Maximum Suction Height (m)	7	7	7	7
Self-priming Time (S)	20	20	20	20
Discharge Port Diameter (mm)	65	65	65	65
N.W/G.W (KG)	91/100	94/103	94/103	94/103
Dimensions (mm)				
Loading Qty (20GP/40HQ)				

GET Wuxi Guangertai Power Machinery Co.,Ltd

☎ 13813650506 ✉ 2415819289@qq.com 🌐 dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA